

Directory Search Results

WRAS Approval Number: 2212355

Approved Product

Range of single hole, single outlet (fixed) pillar tap with brass bodies (chrome plated), incorporating ceramic disc headwork and single lever operating member. Spout outlet incorporates a plastic aerator. Maximum working pressure 5- 10.0 bar (see models). Maximum operating temperature 60°C – 85°C (see models).

Section: 0450 Combination Tap Assemblies (?section=0450)

Section Subtitle: Single hole, metal single outlet, fixed. Taps used in high risk installations, such as kitchen sinks, are considered to be a fluid category 5 risk. Backflow protection is usually provided in the form of an AUK3 tap gap. Where an AUK3 tap gap cannot be maintained, for example where the tap gap is compromised as a result of: • the tap being lowered in any way; • adjustment to the spout which reduces the distance between the tap outlet and spillover level of the sink; • or the operation of a pull out hose attachment; alternative fluid category 5 backflow protection is required.

WRAS Approval Number: 2212355

Expiry date: 31/12/2027

Size: ½" BSF (F) Captive nut

Marking: Scudo on body.

Installation Requirements: R001 (/approvals/testing-requirements/installation_requirements/irn_r001)R006 (/approvals/testing-requirements/installation_requirements/irn_r006)R010 (/approvals/testing-requirements/installation_requirements/irn_r010)R160 (/approvals/testing-requirements/installation_requirements/irn_r160)

Model: TAP241 (5bar,60°C),
BLACK241ORBL (5bar,60°C),
TAP101L (5bar,60°C),
TAP141 (10bar,60°C),
TAP021 (10bar,65°C).
BR-BRASS241 (5bar,60°C)

Factor: Harrison Bathrooms Incorporating Scudo
[View All Listings by this Company \(?company=21422\)](#)